

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
28 April 2005 (28.04.2005)

PCT

(10) International Publication Number  
**WO 2005/039018 A2**

- (51) International Patent Classification<sup>7</sup>: **H02K**
- (21) International Application Number:  
PCT/US2004/033714
- (22) International Filing Date: 13 October 2004 (13.10.2004)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:  
60/510,905 14 October 2003 (14.10.2003) US
- (71) Applicant (for all designated States except US): **THE BRAUN CORPORATION** [US/US]; 631 West 11th Street, P.O. Box 310, Winamac, IN 46996 (US).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **GOODRICH, Ronald** [US/US]; 2716 Northwood Drive, Logansport, IN 46947 (US). **BETTCHER, Robert, E., III** [US/US]; 5134 E. 200 N., Winamac, IN 46996 (US).
- (74) Agent: **MORRIS, David, R.**; Michael Best & Friedrich LLP, 401 N. Michigan Avenue, Suite 1900, Chicago, IL 60611 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

**Declaration under Rule 4.17:**

— of inventorship (Rule 4.17(iv)) for US only

[Continued on next page]

(54) Title: HYDRAULIC DRIVE SYSTEM



(57) Abstract: A hydraulic drive system for reversibly operating a device such as a wheelchair ramp or other type of mobility access device is provided. The hydraulic drive system includes a bi-directional power unit that is in fluid communication with a cylinder for deploying and stowing the ramp. The system further includes valves disposed between the cylinder and pump, which may be spring biased shuttle-type valves. In one embodiment, the valves are normally biased so that the cylinder and ramp may move freely such that the ramp may be manually operated during a loss of electrical power to the power unit.



**Published:**

— without international search report and to be republished  
upon receipt of that report

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*